

SJ7650SHB

Polyolefin Foam Double-Sided Tape

◆ Technical Data

● Product Description

SJ7650SHB used super thin Polyolefin Foam as base material, and coated with adhesive on both sides. It has good properties for waterproof, dustproof and shocking resistance.


● Key Features

Used soft Polyolefin Foam as base material
 Offer high ultimate adhesion to a wide variety of surface.
 Good buffering Performance.
 Good holding power.
 Good properties for dustproof and shocking resistance.
 Good waterproof property, up to the IPX7 standard.
 Halogen free & RoHS (environmental protection) standard.

● Application Ideas

For bonding the LCD, housings, keyboard, camera of cell phone, computer, PDA, PSP etc.
 For bonding the sign and decoration of automobile.
 For bonding the nameplate.
 For bonding electronic components and electronic machine, stuffing.
 Applied in furniture decorate strips, photo frame, etc.
 Other special product bonding solutions.

● Construction



- Modified Acrylic Adhesive
- Polyolefin Foam
- Modified Acrylic Adhesive
- Release Liner

● Technical Data

Test Item	Unit	Value	Test Method
Thickness	mm	0.50	—
180° Peel Adhesion (30 minutes RT)	SUS	N/25mm	30
	PC	N/25mm	28
	Glass	N/25mm	28
	PolyolefinT	N/25mm	25
180° Peel Adhesion (72 hours RT)	SUS	N/25mm	35
	PC	N/25mm	33
	Glass	N/25mm	32
	PolyolefinT	N/25mm	28
Holding Power	Hr	>24	GB/7754, Tensile strength, tape size:25mm*25mm, loading:1kg
Temperature Resistance	°C	-20~80	—
Color	Black		—

◆ Shelf Life & Storage Conditions

- Tape in roll form: Shelf life 6 months from the date of manufacture when stored in original cartons at 20°C and 50% relative humidity.
- Ideal tape application temperature range is 21°C to 38°C.

◆ Notes

The information contained in this data sheet is intended to assist you in designing with Incheng adhesive tape. The technical information and data should be considered representative or typical only. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose. The user should determine the suitability of Incheng adhesive tape for each application.

Servtek Materials Technology (Guangzhou) Co., Ltd

Http: www.servtek.cn



Tel : (+86)20-38892652/38255282

Fax: (+86)20-38892205